

DS-K4H258S One-Door Magnetic Lock

The DS-K4H258S One-Door magnetic lock is designed for wooden door, glass door, and steel door with the opening angle of 90°. The maximum thrust of the lock is 280 kg (617 Lbs). It can be used for controlling door opening/closing, and the indicator shows the door status.



Available Model

DS-K4H258S

Key Features

- The magnetic lock supports static linear thrust of 280 kg (617 Lbs)
- Default voltage is 12 VDC
- It is equipped with internal voltage dependent resistor (MOV)
- It is applied to wooden door, glass door, metal door and fireproof door
- LED indicator displays the status of door lock
- Anti-residual magnetism design
- Abrasion-proof materials
- The shell is made up of aldural and is hard anodizing electroplated
- No mechanical failure, and the magnetic lock works by electromagnetism force





Specifications

Model	DS-K4H258S
Dimension of lock body (L \times W \times H)	238 mm × 45 mm × 25 mm (9.4" × 1.8" × 1.0")
Dimension of armature plate $(L \times W \times H)$	182 mm × 38 mm × 12.5 mm (7.2" × 1.5" × 0.5")
Unlock method	Current interruption
Maximum thrust	280 kg (617 Lbs) linear thrust
Input voltage	12 VDC
Working current	340 mA
LED indicator	Green (work status)
Suitable door	Wooden door, glass door, metal door, fireproof door
Surface temperature	≤ ambient temperature 20 °C (68 °F)
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 95% (relative humidity)
Shell	Hard anodizing electroplating operated
Lock body	Eco-friendly Nickel electroplating operated
Armature plate	Eco-friendly Nickel electroplating operated
Weight	2.1 kg (4.6 Lbs)



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400

sales.usa@hikvision.com **Hikvision Australia** T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T+01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com