

## iDS-6704NXI-I/BA DeepinMind Series NVS



### Key Features

- Deep learning based video analytics for not wearing hard hat detection and behavior analysis, including people running detection, people gathering detection, violent motion detection, using mobile phone detection, etc.
- Facial recognition for people not wearing hard hat
- 2 × RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
- 4K (4096 × 2160) HDMI output
- Centralized management of network cameras, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.
- Compatible with third-party network cameras, such as ACTI, Arecont, AXIS, Bosch, Brickcom, Canon, ONVIF, PANASONIC, Pelco, SAMSUNG, SANYO, SONY, Vivotek and ZAVIO




## Specifications

Model	iDS-6704NXI-I/BA	
Smart Analysis <sup>1</sup>	Not wearing hard hat detection	Up to 4-ch, facial recognition is supported for people not wearing hard hat
	Face picture library	16 libraries
		100, 000 pictures
	Work behavior analysis	Up to 4-ch, including absence/sleep on duty detection people overstay detection, number of people exception detection, and using mobile phone detection
	Street behavior analysis	Up to 4-ch, including people gathering detection, people running detection, violent motion detection, and people falling down detection
Perimeter protection	Up to 4-ch, including line crossing detection, intrusion detection, region entrance detection, and region exiting detection	
Video/Audio output	VGA output	2 × VGA
	HDMI output	2 × HDMI
	Audio output	2-ch, RCA (Linear, 1 KΩ)
Video/Audio input	IP video input	4-ch
	Incoming/Outgoing bandwidth	256 Mbps/200 Mbps
Decoding	Decoding format	H.265/H.265+/H.264/H.264+/MPEG4
	Live view/playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
	Synchronous playback	4-ch
	Capability	4-ch @ 8 MP
Hard disk	SATA	1, 2.5-inch SATA interface
	Capacity	Up to 1 TB
External interface	Two-way audio	1-ch, RCA (2.0 Vp-p, 1 k Ω)
	Network interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
	Serial interface	RS-232; RS-485
	USB interface	Rear panel: 1 × USB 3.0, 1 × USB 2.0
	Alarm in/out	16/4
General	Power supply	12 VDC, 3.33 A
	Consumption (without hard disk)	≤ 30 W
	Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Working humidity	10 to 90 %
	Dimensions (W × D × H)	315 × 65 × 240.8 mm (12.4"× 2.6" × 9.5")
	Weight	≤ 3 kg (6.6 lb)

1: Not wearing hard hat detection, work behavior analysis, street behavior analysis, and perimeter protection cannot be enabled at the same time. Enable one function will make the others unavailable.

## Physical Interfaces



Index	Description	Index	Description
1	LINE IN	7	LAN1 and LAN2 Interface
2	RS-232 Interface	8	AUDIO OUT
3	VGA Interfaces	9	HDMI Interfaces
4	Power Supply	10	USB 3.0 Interface
5	SW Dial	11	Alarm In/Alarm Out and RS-485 Interface
6	USB 2.0 Interface	12	GND

## Available Model

iDS-6704NXI-I/BA

Distributed by



## HIKVISION

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 [216]521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com

0401722000116