

DS-D5065UC-C 65-inch LCD Monitor




- Designed for video security, high reliability and stability
- 65" LED backlight with wide display equipment
- 4K resolution is 4 times the resolution of 1080p, providing a wider view and more fine detail
- Multiple inputs: HDMI, VGA, USB
- Narrow front bezel
- Wide view angle: Horizontal 178°, Vertical 178°
- 24/7 operation

▪ Specification

	Model	DS-D5065UC-C
Display	Screen Size	65"
	Active Display Area	1428.48 (H) mm × 803.52 (V) mm
	Resolution	3840 × 2160@60 Hz
	Backlight	LED
	Pixel Pitch	0.372 (H) mm × 0.372 (V) mm
	Brightness	350 cd/m ²
	Viewing Angle	178° (H)/178° (V)
	Color Depth	8 bit
	Contrast Ratio	1200:1
	Response Time	8 ms
	Refresh Rate	60 Hz
	Haze	1%
	Reliability	7 × 24 H
	Color Gamut	72% NTSC
Interface	Video & Audio Input	HDMI 1.4 × 1, HDMI 2.0 × 1, VGA × 1, Audio in × 1
	Video & Audio Output	Speaker (6 Ω 7 W) × 2
	Data Transmission Interface	USB × 1
Power	Power Supply	100 to 240 VAC, 50/60 Hz
	Power Consumption	≤ 190 W
	Standby Consumption	≤ 0.5 W
Working Environment	Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Working Humidity	20% to 80% RH (Non-Condensing)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Storage Humidity	10% to 90% RH (Non-Condensing)
General	Casing Material	Plastic
	VESA	300 mm × 300 mm (4 × M6-25 mm)
	Bezel Width	8.24 mm (top/left/right), 22.62 mm (bottom)
	Product Dimensions (W × H × D)	Without stand: 1449.6 mm × 838.38 mm × 79.6 mm (57.07" × 33.01" × 3.13") With stand: 1449.6 mm × 883.35 mm × 283.4 mm (57.07" × 34.78" × 11.16")
	Package Dimensions (W × H × D)	1600 mm × 995 mm × 175 mm (62.99" × 39.17" × 6.89")
	Net Weight	Without stand: 18.6 kg (41.01 lb.) With stand: 18.7 kg (41.23 lb.)
	Gross Weight	Without stand: 24.4 kg (53.79 lb.) With stand: 24.5 kg (54.01 lb.)
	Packing List	Power cable × 1, remote control × 1, user manual × 1, HDMI cable × 1, base bracket × 1
Remarks	If the appearance and parameters in this specification vary from the actual product, the later prevails. You can also consult local sale staff.	





▪ **Physical Interface**

Interface	Description	Interface	Description
HDMI-IN1	HDMI1.4 Input, 3840 × 2160@30 Hz	VGA	VGA Input, 1920 × 1080@60 Hz
HDMI-IN2	HDMI2.0 Input, 3840 × 2160@60 Hz	AUDIO-IN	Audio Input
USB	USB 2.0 Input		



AUDIO

VGA



RJ45

USB


HDMI 1

HDMI 2

▪ **Available Model**

DS-D5065UC-C

▪ Dimension



▪ **Accessory**

▪ **Optional**

DS-DM4255W
Wall-mounted
Bracket



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq